



**Material:** Steel (Stainless Steel Type 304 available)

**Standard Finish:** Plain or Electro-Plated

**Service:** Designed for suspending insulated pipe allowing for vertical adjustment.

**Ordering:** Specify part number and finish. For Service temperatures of 750°F (399°C) thru 1050°F (565°C) specify Type 304 Stainless Steel.

**Approvals:** Complies with Federal Specification WW-H-171E & A-A-1192A Type 1 and Manufacturers Standardization Society MSS SP-69 & SP-58 Type 1.

**Note:** Hangers are sized to nominal pipe size - Allowance must be made for insulation thicknesses.

**Figure B3108 Extended Clevis Hanger**

Part No.	Nominal Pipe Size	Rod Size 'A'	'B'		'C'	
B3108-3/4	3/4" (20)	3/8"-16	4 <sup>3</sup> / <sub>8</sub> "	(111.1)	3 <sup>13</sup> / <sub>16</sub> "	(96.8)
B3108-1	1" (25)	3/8"-16	4 <sup>3</sup> / <sub>4</sub> "	(120.6)	4 <sup>1</sup> / <sub>16</sub> "	(103.2)
B3108-1 <sup>1</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>4</sub> " (32)	3/8"-16	5 <sup>3</sup> / <sub>8</sub> "	(136.5)	4 <sup>1</sup> / <sub>2</sub> "	(114.3)
B3108-1 <sup>1</sup> / <sub>2</sub>	1 <sup>1</sup> / <sub>2</sub> " (40)	3/8"-16	6 <sup>7</sup> / <sub>8</sub> "	(174.6)	5 <sup>15</sup> / <sub>16</sub> "	(150.8)
B3108-2	2" (50)	3/8"-16	8 <sup>13</sup> / <sub>16</sub> "	(223.8)	7 <sup>5</sup> / <sub>8</sub> "	(193.7)
B3108-2 <sup>1</sup> / <sub>2</sub>	2 <sup>1</sup> / <sub>2</sub> " (65)	1/2"-13	10"	(254.0)	8 <sup>1</sup> / <sub>2</sub> "	(215.9)
B3108-3	3" (80)	1/2"-13	10 <sup>5</sup> / <sub>8</sub> "	(269.9)	8 <sup>13</sup> / <sub>16</sub> "	(223.8)
B3108-4	4" (100)	5/8"-11	11 <sup>13</sup> / <sub>16</sub> "	(300.0)	9 <sup>1</sup> / <sub>2</sub> "	(241.3)
B3108-5	5" (125)	5/8"-11	13 <sup>1</sup> / <sub>8</sub> "	(333.4)	10 <sup>5</sup> / <sub>16</sub> "	(261.9)
B3108-6	6" (150)	3/4"-10	14 <sup>3</sup> / <sub>8</sub> "	(365.1)	11"	(279.4)
B3108-8	8" (200)	3/4"-10	16 <sup>3</sup> / <sub>4</sub> "	(425.4)	12 <sup>3</sup> / <sub>8</sub> "	(314.3)
B3108-10	10" (250)	7/8"-9	19 <sup>1</sup> / <sub>4</sub> "	(488.9)	13 <sup>13</sup> / <sub>16</sub> "	(350.8)
B3108-12	12" (300)	7/8"-9	21 <sup>5</sup> / <sub>8</sub> "	(549.3)	15 <sup>3</sup> / <sub>16</sub> "	(385.8)

Part No.	Rod Take-Out 'D'		'E'		Adjustment 'F'		'H'		Design Load		Wt./C	
									Lbs.	kN	Lbs.	kg
B3108-3/4	3 <sup>1</sup> / <sub>16</sub> "	(77.8)	2 <sup>1</sup> / <sub>2</sub> "	(63.5)	1/2"	(12.7)	2"	(50.8)	730	(3.25)	45	(20.4)
B3108-1	3 <sup>1</sup> / <sub>4</sub> "	(82.5)	2 <sup>1</sup> / <sub>2</sub> "	(63.5)	5/8"	(15.9)	2"	(50.8)	730	(3.25)	49	(22.2)
B3108-1 <sup>1</sup> / <sub>4</sub>	3 <sup>5</sup> / <sub>16</sub> "	(84.1)	2 <sup>1</sup> / <sub>2</sub> "	(63.5)	7/8"	(22.2)	2"	(50.8)	730	(3.25)	55	(24.9)
B3108-1 <sup>1</sup> / <sub>2</sub>	5 <sup>1</sup> / <sub>8</sub> "	(130.2)	2 <sup>1</sup> / <sub>2</sub> "	(63.5)	1 <sup>3</sup> / <sub>16</sub> "	(30.2)	2"	(50.8)	730	(3.25)	67	(30.4)
B3108-2	6 <sup>7</sup> / <sub>8</sub> "	(174.6)	2 <sup>1</sup> / <sub>2</sub> "	(63.5)	1 <sup>5</sup> / <sub>8</sub> "	(41.3)	4"	(101.6)	730	(3.25)	83	(37.6)
B3108-2 <sup>1</sup> / <sub>2</sub>	7 <sup>9</sup> / <sub>16</sub> "	(192.1)	2 <sup>1</sup> / <sub>2</sub> "	(63.5)	2"	(50.8)	4"	(101.6)	1350	(6.00)	177	(80.3)
B3108-3	7 <sup>7</sup> / <sub>8</sub> "	(200.0)	2 <sup>1</sup> / <sub>2</sub> "	(63.5)	2"	(50.8)	4"	(101.6)	1350	(6.00)	191	(86.6)
B3108-4	8 <sup>3</sup> / <sub>8</sub> "	(212.7)	2 <sup>1</sup> / <sub>2</sub> "	(63.5)	2"	(50.8)	4"	(101.6)	1430	(6.36)	237	(107.5)
B3108-5	9 <sup>1</sup> / <sub>8</sub> "	(231.8)	2 <sup>1</sup> / <sub>2</sub> "	(63.5)	2"	(50.8)	4"	(101.6)	1430	(6.36)	302	(137.0)
B3108-6	9 <sup>11</sup> / <sub>16</sub> "	(246.0)	3"	(76.2)	2"	(50.8)	4"	(101.6)	1940	(8.63)	397	(180.1)
B3108-8	11 <sup>1</sup> / <sub>8</sub> "	(282.6)	3 <sup>1</sup> / <sub>2</sub> "	(88.9)	2 <sup>5</sup> / <sub>16</sub> "	(58.7)	4"	(101.6)	2000	(8.89)	582	(264.0)
B3108-10	12 <sup>5</sup> / <sub>16</sub> "	(312.7)	3 <sup>1</sup> / <sub>2</sub> "	(88.9)	2 <sup>5</sup> / <sub>16</sub> "	(58.7)	4"	(101.6)	3600	(16.01)	968	(439.1)
B3108-12	13 <sup>5</sup> / <sub>8</sub> "	(346.1)	3 <sup>1</sup> / <sub>2</sub> "	(88.9)	2 <sup>5</sup> / <sub>8</sub> "	(66.7)	4"	(101.6)	3800	(16.90)	1221	(553.8)

All dimensions in charts and on drawings are in inches. Dimensions shown in parentheses are in millimeters unless otherwise specified.