

CPVC SOLVENT WELD X COMPRESSION - ANGLE

PART NO.	STOP INLET X OUTLET X RISER LENGTH	FINISH	QTY.	LBS.	LIST EA.	UPC CODE
PR1912A C	1/2" Nom. CPVC x 3/8" O.D. Compr. x 12"	Chrome	50 Pr.	44	44.29	026613084084
PR1920A C	1/2" Nom. CPVC x 3/8" O.D. Compr. x 20"	Chrome	50 Pr.	53	50.47	026613037509



COMPRESSION X COMPRESSION - ANGLE

OCR1912DL C	1/2" Nom. Compr. x 3/8" O.D. Compr. x 12"	Chrome	50	25	16.46	026613035659
OCR1920DL C	1/2" Nom. Compr. x 3/8" O.D. Compr. x 20"	Chrome	50	31	18.80	026613035925
OCR3912DL C	1/2" Nom. Compr. x 1/2" O.D. Compr. x 12"	Chrome	50	26	20.24	026613036076



COMPRESSION X COMPRESSION - STRAIGHT

OCR1412DL C	1/2" Nom. Compr. x 3/8" O.D. Compr. x 12"	Chrome	50	26	17.06	026613045634
OCR3412DL C	1/2" Nom. Compr. x 1/2" O.D. Compr. x 12"	Chrome	50	29	31.12	026613036007



COMPRESSION X FLARE - ANGLE

OFCR1911E C	1/2" Nom. Compr. x 3/8" O.D. Flare x 11"	Chrome	50	23	24.24	026613036144
OFCR3911E C	1/2" Nom. Compr. x 1/2" O.D. Flare x 11"	Chrome	50	24	24.67	026613036168



^ CPVC Pre-torqued Fittings eliminate the need for tightening on the job.

See **pages 66 & 69** for material specifications.
NOTE: Actual riser length is length to connect less 1/2"

Variations

SEE PAGE 71 FOR PRICING OF VARIATIONS



Lock Shield
Loose Key
Add Prefix "S"



Lock Shield
Screwdriver Slot
Add Prefix "SS"




Stuffing Box
Add Prefix "T"



Sweat and loose key stops are furnished with brass stems. All others are furnished with corrosion resistant P.O.M. stems. Brass Stem (Non-Sweat) Add Suffix "Z" e.g., OCR19Z C



Stuffing Box
Lock Shield
Loose Key
Add Prefix "ST"



Stuffing Box
Lock Shield
Screwdriver Slot
Add Prefix "SST"



Cross Handle
Add Prefix "X"



Round (Brass) Handle
Add Prefix "XX"