

# FOOD SERVICE FAUCETS

## 510-GC613ALCP



### Pre-Rinse Fitting with 613-A Adapta Faucet

#### Product Type

Pre-Rinse Fitting with 613-A Adapta Faucet

#### Features & Specifications

- 9 1/2" C-C Swing Spout
- Quixtop™ Coarse Screen Outlet
- 2 3/8" Metal Lever Handles with Secured Red and Blue Service Buttons
- Quatum™ Operating Cartridges
- 3/8" Offset Adjustable Supply Arms with 1/2" NPT Female Thread Inlet and Integral Check
- 1.0 GPM (3.8 L/min) Self Closing Spray Valve
- 23" Riser with Spring Guide

#### Performance Specification

- Rating Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

#### Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

#### Codes & Standards

- ASME A112.18.1M
- CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA

Job Name \_\_\_\_\_

Item Number \_\_\_\_\_

Section/Tag \_\_\_\_\_

Model Specified \_\_\_\_\_

Architect \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor \_\_\_\_\_

Submitted as Shown       Submitted with Variations

Date \_\_\_\_\_



2100 South Clearwater Drive  
Des Plaines, IL  
P: 847/803-5000  
F: 847/803-5454  
Technical: 800/TEC-TRUE  
www.chicagofaucets.com

