

MODELS 60H1KD,
H2KD, BFKD

STANDARD FEATURES

1. Three-piece construction allows for easy installation
2. Sandwich-Wall Construction
3. Sanitary Ware Gel Coat
4. Full-width soap and shampoo ledge across the back wall
5. Anti-slip floor provides added safety (meets ASTM -462)
6. Clear floor space is 56³/₈" x 31¹/₄"
7. Target weight for 60BFKD=165±10 pounds

OPTIONAL FEATURES

- Low Profile bottom
- Pre-installed through-bolted curtain rod
- Pre-plumbed and installed pressure-balancing mixing valve with slide bar and hand-held spray
- Removable threshold
- Pre-installed through-bolted flangeless grab bar(s)
- Pre-installed four-legged fold-down seat
- Barrier-free ramps
- Barrier-free splash guard

Model 60H1KD: Includes a fold-down seat with phenolic seat and stainless steel support tubing, as well as a 1 1/4" diameter "L" shaped stainless steel grab bar. Please specify Left- or Right-hand plumbing.

Model 60H2KD: Includes a full wrap-around 1 1/4" diameter stainless steel grab bar.

Model 60BFKD: Is a barrier-free shower stall without bar or seat option.

Low Profile Option: This option brings the threshold height on the model

60H1KD transfer shower to 1 1/4" after the installation of flooring. **However, a 8" X 8" area must be blocked out around the drain to allow the drain to sit below the subfloor.**



Model 60H1KD

