

Flo Safe-B Bonded Containment System

- Bonded secondary containment system for above or below ground.
- For use in pressure or drainage applications.
- System allows for either cable or probe-type leak detection equipment.
- Containment can be air tested to 5 psi or hydrostatically to 75 psi.
- Incorporates an adhesive bonding agent with the patented Flo Safe split fitting design.
- Pipe and fittings are manufactured of clear PVC.
- Pipe and fittings pressure rating: 75 psi at ambient temperature.
- Temperature rating: 140°F.
- Pipe and fittings in 4" and 6" containment diameters.
- Operating temperature of adhesive 67°F to 140°F; bond strength to 1,300 psi.



FLO SAFE-B DOUBLE CONTAINMENT Pipe

20 ft. lengths; pipe price/per foot.



Size (In.)	Part Number	List Price Ea. (\$)
4	C90040	12.00
6	C90060	28.10

FLO SAFE-B DOUBLE CONTAINMENT 45° Elbow



Size (In.)	Part Number	List Price Ea. (\$)
4	C97040B	93.30
6	C97060B	143.00

FLO SAFE-B DOUBLE CONTAINMENT Pipe Centralizer



Size (In.)	Part Number	List Price Ea. (\$)
4x3/4	P95047	17.00
4x1	P95041	17.00
4x1 1/2	P95045	17.00
4x2	P95042	17.00
6x3	P95063	22.60
6x4	P95064	22.60

Tee



Size (In.)	Part Number	List Price Ea. (\$)
4	C91040B	116.50
6	C91060B	169.30

Coupling Extended



Size (In.)	Part Number	List Price Ea. (\$)
4	C99040B	116.90
6	C99060B	186.50

Adhesive Cartridge



Size (In.)	Part Number	List Price Ea. (\$)
All	B1000	58.80

90° Elbow



Size (In.)	Part Number	List Price Ea. (\$)
4	C96040B	96.50
6	C96060B	156.50

Lateral Wye



Size (In.)	Part Number	List Price Ea. (\$)
4	C94040B	147.60
6	C94060B	256.20

Mixing Tip



Size (In.)	Part Number	List Price Ea. (\$)
All	B1001	2.90

Note: Adhesive has 15-minute exposure after opening; 1 to 2 mixing tips/cartridges are recommended.

Applicator Gun



Size (In.)	Part Number	List Price Ea. (\$)
All	B1002	352.90

See page 138 for additional fittings and accessories applicable to both the Flo Safe-B and Flo Safe-G containment systems.

FLO SAFE-FST

SECONDARY CONTAINMENT FOR TUBING

FST is an outer containment piping system for flexible tubing conveying hazardous material. It features long sweep change of direction fittings and tubing control-valve boxes. Ideally suited for chemical feed lines or applications where flexible tubing is used to pipe hazardous material.

Features:

- Material: clear PVC pipe and fittings, and gray valve boxes with clear lids.
- Pipe is 20-foot lengths and meets ASTM 1785.
- Joining method: can be solvent cement or FST compression fittings.
- Standard sizes are 1½" and 2".
- Non-pressure rated.
- Avoid direct sunlight.



FLO SAFE-FST

DOUBLE CONTAINMENT	Size (In.)	Part Number	List Price Ea. (\$)
--------------------	------------	-------------	---------------------

Clear PVC Pipe (Price per foot)



1½	C90015	3.11/ft.
2	C90020	4.16/ft.

90° Long Sweep



1½	C96115LS	20.50
2	C96120LS	28.00

45° Long Sweep



1½	C97115LS	20.50
2	C97120LS	28.00

22-1/2° Long Sweep




1½	C92115LS	20.50
2	C92120LS	28.00

FLO SAFE-FST

DOUBLE CONTAINMENT	Size (In.)	Part Number	List Price Ea. (\$)
--------------------	------------	-------------	---------------------

Solid Coupling



1½	C99115	9.30
2	C99020	14.48

Compression Coupling



1½	CC99115	27.00
2	CC99020	30.80

Tubing Valve Box

With clear lid	TVB-CST	410.00
With clamp lid	TVB-CL	495.00

