



FLANGED

Qty	Size	Part No.	A Dim	B Dim	Pressure	Anchor Load	Movement	Max Hanger Swing
	2"	VLF80200	40	18.5	500	82	4"	4.1"
	2 1/2"	VLF80250	47	21.5	387	87	4"	4.1"
	3"	VLF80300	52	23.75	288	93	4"	4.1"
	4"	VLF80400	57	26	232	127	4"	4.1"
	5"	VLF80500	63	28.25	200	214	4"	4"
	6"	VLF80600	74.5	33.25	170	228	4"	4"
	8"	VLF80800	86.5	38	212	312	4"	4"
	10"	VLF81000	95.5	41.25	175	345	4"	4"
	12"	VLF81200	108.5	46.5	160	399	4"	4"

*ANCHOR LOAD: THESE VALUES REFLECT THE TOTAL FORCE REQUIRED TO MOVE THE V-LOOP IT'S FULL RATED MOVEMENT FOR 150 P.S.I.@70°F.

For Safe Working Pressure Above 70°F, Multiply The Pressures Shown At 70°F By The Correction Factor For The Required Temperature

TEMPERATURE IN DEGREES FAHRENHEIT	70	200	300	400	500	600
STAINLESS STEEL CORRECTION FACTOR	1.00	.92	.86	.82	.77	.73

CUSTOMER _____
 PROJECT _____
 ENGINEER _____
 ARCHITECT _____
 PRO OR P.O. NO. _____



2323 W. HUBBARD ST.
 CHICAGO, IL 60612
 TEL:312-738-3800
 FAX:312-738-0415
 WWW.METRAFLEX.COM

DESCRIPTION: **V-LOOP**
FLANGED ENDS: 4" MOVEMENT

DRAWING BY: MG	DATE: 06/27/06	DRAWING NUMBER: VLF4
-------------------	-------------------	-------------------------